


TOGE TSM Parapet Anchor

Fastening of scaffolding and formwork in the renovation area

Steel, anti-corrosion coated TOGE KORR



Sleeve with female thread
TSM BC 22x75 KA



Connector M24 KA



Connector with female thread
DW15 IG KA

Item nr.	Designation	Depth of drill hole h_0	Embedment depth of anchor h_{nom}	Max. thickness of fixture t_{fix}	Packing Unit
742 220 750	TSM BC 22x75 IM 16 KA	160 mm	150 mm	-	20
742 241 000	Connector M24x100 KA	-	-	-	20
742 150 000	Connector DW15 IG KA	-	-	-	20

Composite Mortar CF-T 300V

Chemical special mortar
Vinylester styrene-free, suitable for
concrete screws

Product overview

Item nr.	Designation	Packing Unit
222 222 003	Cartridge CF-T 300V	1
222 223 001	Mixing nozzle for CF-T 300V	1
222 222 004	Squeezing pistol for CF-T 300V	1



Processing Instructions

Temperature in ground	Processing time	Min. curing time in dry borehole	Min. curing time in wet borehole
$\geq -5^{\circ}\text{C}$	60 min	360 min	720 min
$\geq 0^{\circ}\text{C}$	60 min	180 min	360 min
$\geq 5^{\circ}\text{C}$	60 min	120 min	240 min
$\geq 10^{\circ}\text{C}$	45 min	80 min	160 min
$\geq 20^{\circ}\text{C}$	15 min	45 min	90 min
$\geq 30^{\circ}\text{C}$	5 min	25 min	50 min
$\geq 35^{\circ}\text{C}$	4 min	20 min	40 min